AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1

4

5

6

7

8

1

2

3

4

A fluid control device wherein a plurality of lines each comprise Claim 1 (original): a plurality of fluid controllers arranged at an upper level and a plurality of coupling 2 members arranged at a lower level, 3

the plurality of lines being arranged in parallel on a base member and having inlets directed in the same direction, with outlets thereof facing toward the same direction,

the fluid control device being characterized in that each line is mounted on a line support member, the line support member being mounted on the base member and slidable in a direction orthogonal to the line.

A fluid control device wherein a plurality of lines Claim 2 (currently amended): each comprise

a plurality of fluid controllers arranged at an upper level and a plurality of coupling members arranged at a lower level,

the plurality of lines being arranged in parallel on a base member and having inlets directed in the same direction, with outlets thereof facing toward the same direction,

the fluid control device being characterized in that each line is mounted on a line support member, the line support member being mounted on the base member and slidable in a direction orthogonal to the line, A fluid control device according to claim 1 wherein

the line support member is a rail removably mounted on the base member, and the coupling members are slidably mounted on the rail, each of the fluid controllers being mounted on two of the coupling members.

Claim 3 (original): A fluid control device wherein a plurality of lines each comprise a plurality of fluid controllers arranged at an upper level and a plurality of coupling members arranged at a lower level,

the plurality of lines being arranged in parallel on a base member and having inlets directed in the same direction, with outlets thereof facing toward the same direction,

the fluid control device being characterized in that the base member is provided with tracks arranged in parallel and corresponding to the respective lines, the coupling members being slidably mounted on the corresponding track, each of the fluid controllers being mounted on two of the coupling members.

1	Claim 4 (currently amended): A fluid control device wherein a plurality of lines
2	each comprise
3	a plurality of fluid controllers arranged at an upper level and a plurality of coupling
4	members arranged at a lower level,
.5	the plurality of lines being arranged in parallel on a base member and having inlets
6	directed in the same direction, with outlets thereof facing toward the same direction,
7	the fluid control device being characterized in that the base member is provided with
8	tracks arranged in parallel and corresponding to the respective lines, the coupling members being
9	slidably mounted on the corresponding track, each of the fluid controllers being mounted on two
10	of the coupling members, A fluid control device according to claim 3 wherein
11	slide members corresponding to the respective coupling members are provided on the
12	track, each of the slide members being connected to the corresponding coupling member.
1	Claim 5 (withdrawn): A fluid control device according to claim 3 wherein
2	the base member is in the form of a plate, and each of the tracks is provided by a groove
3	in an upper surface of the base member.
1	Claim 6 (withdrawn): A fluid control device according to claim 5 wherein
2	a slide member having an internally threaded portion and provided in the groove is
3	connected to the coupling member by a screw member, and an edge portion defining an opening

3

4

1

2

3

- of the groove is provided with a portion for preventing the slide member from slipping out of the groove upward.
- Claim 7 (original): A fluid control device according to claim 4 wherein
 each of the tracks is provided by a rail removably mounted on the base member.
 - Claim 8 (original): A fluid control device according to claim 2 or 7 wherein the rail is U-shaped in cross section and has inward flanges, and a slide member having an internally threaded portion and provided in the rail is connected to the coupling member by a screw member.
 - Claim 9 (withdrawn): A fluid control device according to claim 6 wherein a clearance for inserting a tool therethrough for rotating the screw member is formed between each adjacent pair of the fluid controllers.
- Claim 10 (withdrawn): A fluid control device according to claim 8 wherein
 the rail is provided with a T-shaped intermediate wall dividing the rail in two widthwise
 thereof, and the slide member is divided in two widthwise thereof.

Claim 11 (withdrawn): A fluid control device according to claim 7 wherein 1 the rail is U-shaped in cross section and has outward flanges, and the slide member is 2 provided with rail holding claws engageable with the respective outward flanges of the rail. 3 Claim 12 (withdrawn): A fluid control device according to claim 7 wherein .1 the rail is U-shaped in cross section and has inward flanges, and the slide member is 2 provided with rail holding claws engageable with the respective inward flanges of the rail. 3 Claim 13 (withdrawn): A fluid control device according to claim 11 or 12 wherein 1 the slide member has an internally threaded portion and is connected to the coupling 2 3 member by a screw member. Claim 14 (withdrawn): A fluid control device according to claim 11 or 12 wherein 1 the slide member as positioned in place is fixed to the rail. Claim 15 (original): A fluid control device according to claim 7 wherein 1

the rails are connected to one another by a connecting member.

2

1

3

.1

2

3

1

3

1

2

3

4

5

6

Claim 16 (original): A fluid control device according to claim 1 or 3 wherein the base member is shaped in the form of a frame by an inlet-side rail, an outlet-side rail and connecting members interconnecting the side rails.

Claim 17 (withdrawn): A fluid control device according to claim 7 wherein the slide member is inverted U-shaped, and the slide member has opposite vertical walls holding respective opposite outer side walls of the rail and is thereby attached to the rail.

Claim 18 (withdrawn): A fluid control device according to claim 17 wherein the outer side walls of the rail each have a groove extending longitudinally thereof, and the slide member is provided on each of its vertical walls with a projection fitting in the groove.

Claim 19 (withdrawn): A fluid control device according to claim 7 wherein the rail has an internally enlarged groove opened upward and extending longitudinally thereof, and the slide member comprises

a plate portion in contact with a lower surface of the coupling member, and a portion projecting downward from a lower surface of the plate portion and having a lower end fitted in the internally enlarged groove of the rail.

1

2

3

1

2

5

1

2

3

Claim 20 (withdrawn): A fluid control device according to claim 7 wherein the rail has an internally enlarged groove opened upward and extending longitudinally thereof, and the rail has a groove formed in each of opposite outer side walls thereof and extending longitudinally thereof.

Claim 21 (withdrawn): A fluid control device according to claim 7 which has fixed slide members fixed to the rail with a screw and unfixed movable slide members, and the coupling member having the fixed slide member is connected to the coupling member having the movable slide member by the fluid controller, whereby the coupling member having the movable slide member is prevented from moving.

Claim 22 (withdrawn): A fluid control device according to claim 8, wherein a clearance for inserting a tool therethrough for rotating the screw member is formed between each adjacent pair of the fluid controllers.

* * * *